

ROSTRESS 24.70 HYDRAULIC RAIL STRESSOR

SPECIFICATION	STANDARD	HOLLOW PISTON CYLINDER	3RD RAIL
■ Tensile Force	700 kN	700 kN	700 kN
■ Compressive Force	400 kN		
■ Stroke	15"	8"	15"
■ Dimensions (L x W x H) when Installed	104.5 x 44 x 15"	98.5 x 40 x 15"	121 x 36.5 x 15"
■ Weight			
Heaviest Individual Component	73 lbs	73 lbs	73 lbs
Hand Pump	50.5 lbs	50.5 lbs	50.5 lbs
Dual hydraulic power pack 76.02 with 4 cycle engine.	97 lbs	97 lbs	97 lbs
Dual hydraulic power pack 76.20 E3 with 800WH ROBEL battery	84 lbs excl. battery	84 lbs excl. battery	84 lbs excl. battery
Battery 800wh	14 lbs	14 lbs	14 lbs
Hydraulic Power Packs Optionally with Hand Pump for Emergency Operation: +6.5 lbs			



BENEFITS

- Safe and easy operation
- Modular design

HYDRAULIC POWER SUPPLY OPTIONS

- Dual hydraulic power pack 76.02 with combustion engine
- Dual hydraulic power pack 76.20 E3 with ROBEL battery

The modular concept for creating a neutral rail tension during welding and bracing work.